TECHNICAL DATA SHEET / FACT SHEET



PASTE

COMPOUND

- HS, MS PAINTS
- WET OR DRY USE
- PERMANENT RESULTS NO FILLERS



PRODUCT DESCRIPTION / KEY BENEFITS

- Reliable cut easy and fast removes P1500 sanding marks
- Fast, permanent result no fillers
- High gloss finish, for an enhanced gloss finish or on dark colors use with SPRIXE Finishing Compound
- Silicone free 100% Bodyshop and Paint shop safe
- Can be used by hand or machine

PRODUCT INFORMATION

PRODUCT	SIZECODE	QTY
250 g	SX250	24
1 kg	SX1000	6
3 kg	SX3000	4

USE WITH



6" Standard Compounding **Head White SXSCHW** 6"/150 mm



6" Velcro Compounding Foam White SXVCFW6 6"/150 mm



6" Flexible Back SXFBP146 6"/150 mm

STAGE 1:

HOW TO USE



Spray pad with water



Apply a small amount of product



Compound at (1500 - 1800 rpm)



Wipe clean with a Finishing Cloth

TECHNICAL INFORMATION

Appearance: cream paste

Viscosity: high viscosity

VOC Content: 150g/l

Relative Density: 1,45

pH: 8,9

Paint Type Compliance: MS & HS

