

## 336 ULTRA GLOSS WAX PROTECTOR

	r
Description	U-POL 336 Ultra Gloss Wax Protector delivers a superb long lasting mirror finish and is ideally suited for both bodyshop and valeting applications. It has been designed to give enhanced protection against weathering effects and exhibits desirable water and dirt repellent properties. This formula is quick and easy to apply on all original and fully cured paintwork. It is 100% bodyshop safe.
Preparation	<u>Old paintwork</u> should be cleaned thoroughly to remove road traffic film and dirt. Wipe down surface with <b>System 2000, 2001 or 2002</b> degreaser. <u>New paint</u> should be fully cured in accordance with paint manufacturers' drying schedule. Paintwork should be washed and dried where necessary before applying <b>U-POL 336</b> .
Application	Recommended for hand use only. Shake <b>U-POL 336</b> before use. Apply a small amount of product to a clean slightly damp <b>U-POL Micro Fibre Polishing Cloth</b> . Using a light even pressure, apply product to the surface using an overlapping motion to ensure complete coverage. Leave the wax to dry to a haze. Using a clean section of cloth, wipe away the excess and give a slight buff to bring out the gloss. Due to the formulation's easy removal properties, large areas can be treated at a time. Remove any residue from surrounding trim using a soft clean damp cloth.
Additional Information	Other products in the <b>U-POL Automotive Polishing System</b> are <b>333 Cutting Compound</b> <b>Paste</b> and <b>333 Liquid Cutting Compound</b> for regular compounding and paint defect rectification, <b>334 Fine Finishing Compound</b> for minor defect correction and paint restoration and <b>335 High Gloss Final Glaze</b> for that showroom finish. All products are 100% bodyshop safe.
Order Codes	QW336/1 - 1 litre bottle (6 units per carton)
Storage	It is recommended that <b>U-POL 336</b> is stored in a frost free environment.
Tools	QWCMF - Micro Fibre Polishing Cloth
Health and Safety Statement	FOR PROFESSIONAL USE ONLY. Read full instructions before use. U-POL disclaim any liability where the end user does not wear the recommended personal protective equipment.
VOC Information	VOC content 231g/l



U-POL LTD, 4<sup>TH</sup> FLOOR, THE GRANGE, 100 HIGH STREET, LONDON N14 6BN, UK Home Sales T: +44(0)20 8492 5920; F:+44(0)20 8181 6911; E: uk.sales@u-pol.com; Export Sales T: +44(0)20 8492 5900; F:+44(0)20 8150 5605; E: sales@u-pol.com; Technical T: +44(0)1933 230 310; F:+44(0)1933 425 797; E: technicaldepartment@u-pol.com; WWW.U-POL.COM